

## 1993 Suburban production overview

### Points of interest for 1993 Suburban

Series	
C/K 1500	85%
C/K2500	15%

Models	
Panel Doors	78%
Tailgate	22%

Trim Level	
Cheyenne	15%
Silverado	85%

Engines	
5.7L	90%
7.4L	10%

Transmission	
MX0	100%

*Manufactured in Janesville, WI*

---

### Engine Stats:

Engine	Net Horsepower At RPM	Net Torque (lbs-ft) At RPM	Compression Ratio
5.7L V8*	210 at 4,000	300 at 2,800	9.1:1
5.7L V8**	190 at 4,000	300 at 2400	8.3:1
7.4L V8**	230 at 3,600	385 at 1600	7.9:1

**Interior:**

	Cheyenne (Std)		Silverado (YE9)	
	Suburban	Blazer	Suburban	Blazer
<b>Armrests</b> , RH and LH padded intgral with door panel	S	S	S	S
<b>Cigarette Lighter</b> , with ashtray light	S	S	S	S
<b>Coat Hooks</b> , Two RH, and two LH located above intermediate seat and in cargo area	S	N/A	S	N/A
Two RH, and two LH located in cargo area	N/A	N/A	N/A	S
<b>Cup Holder</b> , dual	S	S	S	S
<b>Dome Lamp</b> , Front, and rear ceiling mounted	S	S	S	S
with map lights	N/A	N/A	S	S
<b>Power Door Locks</b>	O	O	S	S
<b>Door Trim</b> , color keyed molded plastic with vinyl trim	S	N/A	N/A	N/A
Cloth inserts with Vinyl Trim and carpet trip, front map pockets with door assist straps, and color coordinated rear door/tailgate and rear sidewall trim panels	N/A	N/A	S	N/A
Color keyed door sill plates	S	N/A	S	N/A
Cloth inserts with carpet trim, front map pockets with door assist straps and color coordinated tailgate trim panels.	N/A	N/A	N/A	S
Color keyed door sill plates	N/A	S	N/A	S
<b>Floor Console</b> , color keyed with storage, and beverage pockets (included with customer cloth high back bucket seats.)	N/A	N/A	N/A	S
<b>Floor Covering</b> , two piece blackvinyl mats for entire area	S	N/A	N/A	N/A
One piece black vinyl mat for entire area	N/A	S	N/A	N/A
Color keyed carpeting for entire area	N/A	N/A	S	S
Floor mats, removable, color keyed, front and rear	N/A	N/A	S	S

<b>Glove Box</b> , latched with beverage wells on door	S	S	S	S
<b>Headliner</b> , Full length, color keyed cloth with matching moulding	S	S	S	S
<b>Instrument Panel</b> , Gages: Speedometer, odometer, tip odometer fuel level, coolant temperature, voltmeter, oil pressure, with telltale lights, and headlights-on buzzer	S	S	S	S
<b>Instrument Panel Trim</b> , Woodgrain	S	S	S	S
<b>LiftGlass Release</b> , Power on instrument panel	N/A	S	N/A	S
<b>Mirror</b> , 10" Rear view	S	S	S	S
<b>Radio</b> , Electronically tuned AM, with two dash, and two rear mounted speakers	S	S	N/A	N/A
Electronically tuned AM/FM stereo with two dash, and two rear mounted speakers	O	O	S	S
<b>Scotchgard™ Fabric Protector</b> , on cloth trim, and seats	S	S	S	S
<b>Seats</b> , Front 3-passenger bench with outboard head restraints	S	N/A	S	N/A
Matching intermediate 40/60 split folding bench	O	N/A	S	N/A
Vinyl Trim	S	N/A	N/A	N/A
Cloth Trim	O	N/A	S	N/A
3 Passenger Rear Set in matching trim	O	N/A	O	N/A
Reclining Low-back front bucket seats with head restaints	N/A	S	N/A	N/A
Reclining 40/60 split front cloth bench seat with outboard head restraints, and easy-entry feature on RH side.	N/A	N/A	N/A	S
<b>Spare Tire/Wheel</b> , Full size	S	S	S	S
Carpeted cover	N/A	N/A	S	S
<b>Steering Wheel</b> , Self-aligning, 4 spoke custom wheel	S	S	N/A	N/A
Self-Aligning 4 spoke simulated leather sport wheel	N/A	N/A	S	S
<b>Sun Visors</b> , Padded color keyed RH and LH	S	S	S	S
Vinyl Trimmed	N/A	S	N/A	N/A
Cloth With illuminated mirrors	N/A	N/A	S	S
<b>Windshield Washers</b> , intermittent	S	S	S	S

S = Standard O = Optional N/A = Not Available

-----  
**Color Availability:**

Exterior Color	Code	Interior Colors			
		Beige	Blue	Red	Gray
Smoke Blue metallic	27		*		*
Teal Blue metallic	36	*			*
Indigo Blue metallic^	39	*	*		*
Onyx Black	41	*		*	*
Summit White	50	*	*	*	*
Sand Beige metallic	57	*			
Victory Red	74	*			*
Burnt Red Metallic	76	*		*	*
Quicksilver Metallic	96		*	*	*
Slate Metallic	97			*	*

*^ New color for 1993*

**Exterior:**

	Cheyenne (Std.)		Silverado (YE9)	
	Suburban	Blazer	Suburban	Blazer
<b>Air Dam</b> , black	S	S	S	S
<b>Bumpers</b> , Chromed front with rub strips	N/A	S	N/A	S
chromed Rear with black plastic step pad and rub strip	N/A	S	N/A	S
Front bumper guards and bright rub strip	N/A	N/A	N/A	S
Chromed front, and rear with rub strips	S	N/A	S	N/A
Rear block step pad	S	N/A	S	N/A
<b>Glass</b> , solar-Ray™ light tinted	S	S	S	S
Tinted all around including deep tint on windshield upper band	S	S	S	S
<b>Grille</b> , Light argent with dark argent highlights	S	S	N/A	N/A
Deluxe dark argent grille with bright trim	N/A	N/A	S	S
<b>Headlights</b> , halogen single rectangular	S	S	N/A	N/A
Halogen, dual rectangular composite	N/A	N/A	S	S
<b>Horn</b> , Dual high, and low note electric	S	S	S	S
<b>Lamp</b> , underhood reel type removable	N/A	O	N/A	S
<b>Mirrors</b> , RH and LH below eyeline	N/A	S	N/A	S
Black 6.5" x 9"	N/A	S	N/A	N/A
Chrome 6.5" x 9"	N/A	N/A	N/A	S
<b>Moldings</b> , black body side	S	N/A	S	N/A
Black Wheel opening	S	N/A	N/A	N/A
Bright wheel opening	N/A	N/A	S	N/A
<b>Tailgate</b> , liftglass-dropgate with electric release on inst panel	N/A	S	N/A	S
<b>Tow Hooks</b> , two front on 4WD models	N/A	S	N/A	S
<b>Wheels</b> , silver-painted steel	N/A	S	N/A	S
Black hub trim	N/A	S	N/A	N/A
Rally wheel trim	N/A	N/A	N/A	S
Bright metal hubcaps	N/A	N/A	S	N/A

S = Standard    O = Optional    N/A = Not Available

-----  
**Specifications:**

	Sub C1500 CC10906	Sub C2500 CC20906	Sub K1500 CK10906	Sub K2500 CK20906	Blazer K1500 CK10516/ZW9
<b>Exterior</b>					
Wheel Base	131.5	131.5	131.5	131.5	111.5
Overall Length	218.9	218.9	218.9	218.9	187.7
Maximum Width	76.4	76.4	76.4	76.4	76.4
Overall Height	68.8	68.8	68.8	68.8	71
Ground to rear load floor	25.9	25.9	25.9	25.9	27.8
Ground clearance Front/Rear	7.0/8.4	7.8/7.8	8.6/9.0	8.7/7.7	6.9/7.1
<b>Interior:</b>					
Front/Rear Headroom (in)	34.7/39.3	34.7/39.3	34.7/39.3	34.7/39.3	40.2/38.0
Legroom	41.8/36.6	41.8/36.6	41.8/36.6	41.8/36.6	41.7/37.6
Shoulder room	66.0/66.1	66.0/66.1	66.0/66.1	66.0/66.1	66.0/63.2
Hip room	60.5/59.6	60.5/59.6	60.5/59.6	60.5/59.6	60.5/53.1
Cargo capacity w/front seat only	175.9	175.9	175.9	175.9	102.8
<b>Fuel tank (gal)</b>	42	42	42	42	30
<b>GVWR (lbs)</b>					
Standard	6800	8600	7200	8600	6250
Maximum	6800	8600	7600	9100	6250
<b>Payload (lbs)</b>					
Standard	2100	3320	2350	3065	1560
Maximum	2100	3320	2350	3565	1560
<b>Max Trailering Capacity (lbs)</b>	7000	10000	6500	10000	7000
<b>Engine specifications</b>					
Standard Engine (CID)	5.7 (350) V8	5.7 (350) V8	5.7 (350) V8	5.7 (350) V8	5.7 (350) V8
Optimal Engine (CID)	N/A	7.4 (454) V8	N/A	7.4 (454) V8	N/A
Battery (SAE Capacity rating)	630 cca	630 cca	630 cca	630 cca	630 cca
<b>Transmission specifications</b>					
Type - Standard	4sp Auto OD	4sp Auto OD	4sp Auto OD	4sp Auto OD	5sp Man.
Type - Optimal	N/A	N/A	N/A	N/A	4sp Auto
Gear Ratios :1	Std.	Std.	Std.	Std.	Std./Opt.
1st gear	3.06	2.48	3.06	2.48	4.02-3.06
2nd gear	1.63	1.48	1.63	1.48	2.32/1.63
3rd gear	1.00	1.00	1.00	1.00	1.40/1.00
4th gear	0.70	0.75	0.70	0.75	1.00/.70
5th gear	N/A	N/A	N/A	N/A	.73/--
Reverse	2.29	2.08	2.29	2.08	3.74/2.29
Transmission type	4L60E	4L80E	4L60E	4L80E	N/A

**Chassis Specifications**

Brakes - Front	Disc/ABS	Disc/ABS	Disc/ABS	Disc/ABS	Disc/ABS
Brakes - Rear	Drum/ABS	Drum/ABS	Drum/ABS	Drum/ABS	Drum/ABS
Steering type	Variable-ratio Integral power	Variable-ratio Integral power	Variable-ratio Integral power	Variable-ratio Integral power	Variable-ratio Integral power
Turning Diameter curb-curb	45.8	41.4	47.8	46.4	41.5
Front Suspension	Ind./Coil Spring	Ind./Coil Spring	Ind/Torsion	Ind/Torsion	Ind/Torsion
Rear Suspension	2 stage Multi-leaf	2 stage Multi-leaf	2 stage Multi-leaf	2 stage Multi-leaf	2 stage Multi-leaf
Rear Axle - Type	Semi-floating	Semi-floating	Semi-floating	Semi-floating	Semi-floating
Ratios (range) :1	3.08-3.73	3.42.4.10	3.42-3.73	3.42-4.10	3.42-3.73

**Tires, and Wheels**

Wheel Size	15x7	16x6.5	16x16.5	16x16.5	16x16.5
Tire Size	P235/75R15XL	LT225/75R16D	LT245/75R16	LT245/75R16E	N/A

**Engine Details**

	<b>L05 (350 V8)</b>	<b>L05 (H.D 350 V8)</b>	<b>L19 (454 V8)</b>
Type	<b>OHV V8</b>	<b>OHV V8</b>	<b>OHV V8</b>
Block Material	Cast Iron	Cast Iron	Cast Iron
Cylinder Head Material	Cast Iron	Cast Iron	Cast Iron
Valvetrain	2 Valves per Cyl	2 Valves per Cyl	2 Valves per Cyl
Hydraulic lifters	Yes	Yes	Yes
Bore x Stroke Inches	4.0 x 3.48	4.0 x 3.48	4.25 x 4.0
Bore x Stroke Millimeters	101.6 x 88.39	101.6 x 88.39	108 x 101.6
Displacement (Liters/CID)	5.7/350	5.7/350	7.4/454
Compression Ratio	9.3:1	8.6:1	7.9:1
Induction system	EFI	EFI	EFI
Horsepower (SAE Net)	210 at 4,000	190 at 4,000	230 at 3,600
Torque (SAE Net)	300 at 2,800	300 at 2,400	385 at 1,600
Recommended Fuel	87 Octane	87 Octane	87 Octane
Redline (Fuel cutoff)	4800	4800	4800
Emission Control	Cat. Conv./EGR	Cat. Conv./EGR	Cat. Conv./EGR
Cam Drive	Chain	Chain	Chain

<b>Suspension details</b>		
	<b>C1500/2500</b>	<b>K1500/2500</b>
Frame	All welded, ladder type channel with boxed front end	Same as C1500/2500
Front suspension	Independent with coil springs	Independent with torsion bars
Rear Type	Hypoid-Drive 2stage Multi-leaf spring	Same as C1500/2500
Shocks (front/rear) millimeter	32/32	Same as C1500/2500
Anti-Roll Bar (front/rear) Inches	32/22	30/22
rear Axle (std)	Semi-Floating	Same as C1500/2500

<b>Steering Details</b>		
	<b>C/K1500</b>	<b>C/K2500</b>
Type	Variable ratio integral power	Same as C/K1500
Steering ratio on center	16.0:1	Same as C/K1500
Steering ratio at lock	13.0:1	Same as C/K1500
Turning Diameter curb to curb Feet (C/K)	45.8/47.87	41.4/46.4
Turning Diameter wall to wall Feet (C/K)	47.4/49.6	43.6/47.9

<b>Brakes Detail</b>		
	<b>C/K1500</b>	<b>C/K2500</b>
Type:	Vacuum power	Same as C/K1500 Hydroboost 8600GVWR
Front Disc Size (In)	11.57 x 1.25	12.0 x 1.5
Rear drum size (In)	11.15 x 2.75	13.0 x 2.5
Booster Diameter (in)	9.5, Tandem	Same as C/K1500
Parking Brake	Cable to rear wheels	Same as C/K1500

<b>Performance</b>		
	<b>C1500</b>	<b>K1500</b>
EPA Mileage (city/Highway/Combined) (Mi)	13/17/14	N/A over 8500GVW
Est cruising range (city/hwy) (Mi)	546/714	N/A
Max GVWR Range (lbs)	6800	8600
Coefficient of Drag	0.457	0.457



<b>Capacities/Calculated Data</b>	<b>5.7 V8 (L05)</b>	<b>7.4 V8 (L19)</b>
Engine oil (qt)	5	6
Fuel (gal)	42/42	42/42
Engine coolant (qt)	4.3/4.3	6.1/6.1
Weight to Power Ratio (lbs/hp)	22.18/24.35	21.75/23.50
Specific output (hp/ltr)	36.84/36.84	31.08/31.08
Approach/Departure angle (deg)	17/17--21/21	19/21--23/22
Ramp Breakover angle (deg)	13/16	15/18